

百德大益涂料商行

嘉玛国际贸易(深圳)有限公司

深圳市福田区市花路花样年福年广场 B 栋一单元 423
 电话: 0755-83597378 (深圳) 电话: 020-83399022 (广州) 传真: 0755-83597379

RYUDYE-W RED FF2G

大红 1447

| 颜色范例 Depth 50/10/2 g/kg | 坚牢度 (测试深度 = 50 克/公斤) Fastness Test (Depth = 50 g/kg) | | | | | | 耐胶浆 迁移性 Rubber migration |
|---|---|---------|----------------|-----------------------------|----------------|-----------------------------|-----------------------------------|
| | 耐光 Light | | 耐皂洗 Washing | 耐拔染 Discharge ability | 耐溶剂 Solvent | 耐热 Heat 180°C 30 s | 30 g/kg |
| | 50 g/kg | 10 g/kg | | | | | |
|  | 8 | 7-8 | 5 | 3-4 | 5 | 5 | ● |

备注:

- | | |
|-------|---------------|
| ● 良好 | Good |
| × 差 | Not recommend |
| ▲ 需测试 | Need to test |

Remark :

- Under the normal textile application, the product can be passed the requirement of Oeko-Tex Standard 100.
- The information and data in this bulletin are based on accurate laboratory researched and are intended for your guidance. We cannot, however, accept any responsibility for the results obtained, in view of the numerous factors of application are beyond our control. Our guarantee is limited to the unvarying quality of our products.

备注:

- 在正常印花工艺下使用在纺织品上, 能通过 OEKO-TEX STANDARD 100 之要求。
- 本数据是基于精密试验所得, 以供阁下参考。对于使用后所得之一切结果, 不负任何责任。这是因为印花厂内有许多的变量超出我们所能控制的范围。本公司仅保证产品之品质稳定不变。